



Y117

LISTINO PREZZI END USER 2017
END USER PRICE LIST 2017

01-2017 | EURO
ITALIANO ENGLISH
COD. 90 000 248

INDICE
INDEX

GREEN PLUS	4
GREEN PU	6
GREEN COMPACT ME / PU	8
GREEN METALL	10
GREEN CLUB ME / PU / PU-S	12
K65 AT / ST / OD	14
MD 75 / 74 / CLUB	16
DP 190 / 100 / 12 / 8	18
Condizioni generali di vendita	20
General conditions of sales	
Contatti	21
Contacts	

GREEN PLUS

CARATTERISTICHE TECNICHE

2 GRUPPI

Dimensioni (L×P×A) 765×530×560 mm	Peso 73 kg
Caldaia 11 l	Potenza caldaia 4300 W (2700 W)
Voltaggio 220-240 V / 380-415 V (3N)	Frequenza 50/60 Hz

3 GRUPPI

Dimensioni (L×P×A) 1005×530×560 mm	Peso 93 kg
Caldaia 16 l	Potenza caldaia 6000 W
Voltaggio 220-240 V / 380-415 V (3N)	Frequenza 50/60 Hz

DOTAZIONI

1 portafiltro per due caffè per ogni gruppo, 1 portafiltro per un caffè, 2 erogatori vapore, 1 erogatore acqua calda, scaldatazze, filtri

OPTIONAL

Portafiltro per cialda, riscaldamento a gas, kit cialda, kit capsula, Easy Steam Milk (ESM), luci LED

ACCESSORI

Addolcitore d'acqua automatico o manuale, macinadosatore MD

COLORI

Grigio, nero lucido, rosso bordeaux

TECHNICAL FEATURES

2 GROUPS

Dimensions (W×D×H) 30.1×20.9×22.0 in	Weight 161 lb
Boiler 11 l (2.4 gal _{UK})	Boiler power 4300 W (2700 W)
Voltage 220-240 V / 380-415 V (3N)	Frequency 50/60 Hz

3 GROUPS

Dimensions (W×D×H) 39.6×20.9×22.0 in	Weight 205 lb
Boiler 16 l (3.5 gal _{UK})	Boiler power 6000 W
Voltage 220-240 V / 380-415 V (3N)	Frequency 50/60 Hz

STANDARD

1 filter holder for 2 cups per group, 1 filter holder for 1 cup, 2 steam wands, 1 hot water dispenser, cup warmer, filters

OPTIONAL

Filter holder for pod, gas heating, pod kit, capsule kit, Easy Steam Milk (ESM), LED lights

ACCESSORIES

Automatic or manual water softener, MD dosing grinder

COLORS

Natural grey, gloss black, bordeaux red

FEATURES | ON DEMAND

Kit riscaldamento a gas € 158,00
Gas Heating

Portafiltro per cialda € 89,00
Filter holder for pod

ESM € 147,00
Easy Steam Milk

Luci LED per 2 gruppi € 164,00
LED Lights for 2 groups

Luci LED per 3 gruppi € 208,00
LED Lights for 3 groups



GREEN PLUS 2GR
€ 4.410,00



GREEN PLUS 3GR
€ 5.450,00

Per info su Certificazioni Prodotti disponibili visitare www.promacitalia.com
For info on available Products' Certifications please visit www.promacitalia.com

GREEN PU

CARATTERISTICHE TECNICHE

2 GRUPPI

Dimensioni (L×P×A) 765×530×560 mm	Peso 73 kg
---	----------------------

Caldaia 11 l	Potenza caldaia 4300 W (2700 W)
------------------------	---

Voltaggio 220-240 V / 380-415 V (3N) / (120 V)	Frequenza 50/60 Hz
--	------------------------------

3 GRUPPI

Dimensioni (L×P×A) 1005×530×560 mm	Peso 93 kg
--	----------------------

Caldaia 16 l	Potenza caldaia 6000 W
------------------------	----------------------------------

Voltaggio 220-240 V / 380-415 V (3N)	Frequenza 50/60 Hz
--	------------------------------

DOTAZIONI

1 portafiltro per due caffè per ogni gruppo, 1 portafiltro per un caffè, 2 erogatori vapore, 1 erogatore acqua calda, scaldatasse, filtri

OPTIONAL

Portafiltro per cialda, riscaldamento a gas, kit cialda, kit capsula, Easy Steam Milk (ESM), luci LED

ACCESSORI

Addolcitore d'acqua automatico o manuale, macinadosatore MD

COLORI

Grigio, nero lucido, rosso bordeaux

TECHNICAL FEATURES

2 GROUPS

Dimensions (W×D×H) 30.1×20.9×22.0 in	Weight 161 lb
--	-------------------------

Boiler 11 l (2.4 gal _{UK})	Boiler power 4300 W (2700 W)
--	--

Voltage 220-240 V / 380-415 V (3N) / (120 V)	Frequency 50/60 Hz
--	------------------------------

3 GROUPS

Dimensions (W×D×H) 39.6×20.9×22.0 in	Weight 205 lb
--	-------------------------

Boiler 16 l (3.5 gal _{UK})	Boiler power 6000 W
--	-------------------------------

Voltage 220-240 V / 380-415 V (3N)	Frequency 50/60 Hz
--	------------------------------

STANDARD

1 filter holder for 2 cups per group, 1 filter holder for 1 cup, 2 steam wands, 1 hot water dispenser, cup warmer, filters

OPTIONAL

Filter holder for pod, gas heating, pod kit, capsule kit, Easy Steam Milk (ESM), LED lights

ACCESSORIES

Automatic or manual water softener, MD dosing grinder

COLORS

Natural grey, gloss black, bordeaux red

FEATURES | ON DEMAND

Kit riscaldamento a gas € 158,00
Gas Heating

Portafiltro per cialda € 89,00
Filter holder for pod

ESM € 147,00
Easy Steam Milk

Luci LED per 2 gruppi € 164,00
LED Lights for 2 groups

Luci LED per 3 gruppi € 208,00
LED Lights for 3 groups



GREEN PU 2GR
€ 3.465,00



GREEN PU 3GR
€ 4.064,00

Per info su Certificazioni Prodotti disponibili visitare www.promacitalia.com
For info on available Products' Certifications please visit www.promacitalia.com

GREEN COMPACT ME / COMPACT PU

CARATTERISTICHE TECNICHE

2 GRUPPI COMPACT ME

Dimensioni (L×P×A) 580×530×560 mm	Peso 71 kg
---	----------------------

Caldaia 5 l	Potenza caldaia 3000 W (2700 W)
-----------------------	---

Voltaggio 220-240 V / 380-415 V (3N) / (120 V)	Frequenza 50/60 Hz
--	------------------------------

2 GRUPPI COMPACT PU

Dimensioni (L×P×A) 580×530×560 mm	Peso 71 kg
---	----------------------

Caldaia 5 l	Potenza caldaia 3000 W (2700 W)
-----------------------	---

Voltaggio 220-240 V / 380-415 V (3N) / (120 V)	Frequenza 50/60 Hz
--	------------------------------

DOTAZIONI

1 portafiltro per due caffè per ogni gruppo, 1 portafiltro per un caffè, COMPACT ME: 2 erogatori vapore / COMPACT PU: 1 erogatore vapore, 1 erogatore acqua calda, filtri

OPTIONAL

Portafiltro per cialda, kit cialda, kit capsula, Easy Steam Milk (ESM), luci LED

ACCESSORI

Addolcitore d'acqua automatico o manuale, macinadosatore MD

COLORI

Grigio, nero lucido, rosso bordeaux

TECHNICAL FEATURES

2 GROUPS COMPACT ME

Dimensions (W×D×H) 22.8×20.9×22.0 in	Weight 156 lb
--	-------------------------

Boiler 5 l (1.1 gal _{UK})	Boiler power 3000 W (2700 W)
---	--

Voltage 220-240 V / 380-415 V (3N) / (120 V)	Frequency 50/60 Hz
--	------------------------------

2 GROUPS COMPACT PU

Dimensions (W×D×H) 22.8×20.9×22.0 in	Weight 156 lb
--	-------------------------

Boiler 5 l (1.1 gal _{UK})	Boiler power 3000 W (2700 W)
---	--

Voltage 220-240 V / 380-415 V (3N) / (120 V)	Frequency 50/60 Hz
--	------------------------------

STANDARD

1 filter holder for 2 cups per group, 1 filter holder for 1 cup, COMPACT ME: 2 steam wands / COMPACT PU: 1 steam wand, 1 hot water dispenser, filters

OPTIONAL

Filter holder for pod, pod kit, capsule kit, Easy Steam Milk (ESM), LED lights

ACCESSORIES

Automatic or manual water softener, MD dosing grinder

COLORS

Natural grey, gloss black, bordeaux red

FEATURES | ON DEMAND

Portafiltro per cialda € 89,00
Filter holder for pod

ESM (solo COMPACT ME) € 147,00
Easy Steam Milk (only COMPACT ME)

Luci LED per 2 gruppi € 164,00
LED Lights for 2 groups



GREEN COMPACT ME 2GR
€ 3.549,00



GREEN COMPACT PU 2GR
€ 2.751,00

Per info su Certificazioni Prodotti disponibili visitare www.promacitalia.com
For info on available Products' Certifications please visit www.promacitalia.com

GREEN ME TALL

CARATTERISTICHE TECNICHE

2 GRUPPI TALL

Dimensioni (L×P×A) 765×530×640 mm	Peso 75 kg
---	----------------------

Caldaia 11 l	Potenza caldaia 4300 W
------------------------	----------------------------------

Voltaggio 220-240 V / 380-415 V (3N)	Frequenza 50/60 Hz
--	------------------------------

3 GRUPPI TALL

Dimensioni (L×P×A) 1005×530×640 mm	Peso 95 kg
--	----------------------

Caldaia 16 l	Potenza caldaia 6000 W
------------------------	----------------------------------

Voltaggio 220-240 V / 380-415 V (3N)	Frequenza 50/60 Hz
--	------------------------------

DOTAZIONI

1 portafiltro per due caffè per ogni gruppo, 1 portafiltro per un caffè, vassoietto poggia-tazza, 2 erogatori vapore, 1 erogatore acqua calda, scaldatazze, filtri

OPTIONAL

Cappuccinatore, portafiltro per cialda, kit cialda, kit capsula, Milk Temperature Sensor (MTS), Easy Steam Milk (ESM), luci LED

ACCESSORI

Addolcitore d'acqua automatico o manuale, macinadosatore MD

COLORI

Nero lucido

TECHNICAL FEATURES

2 GROUPS TALL

Dimensions (W×D×H) 30.1×20.9×25.2 in	Weight 165 lb
--	-------------------------

Boiler 11 l (2.4 gal _{UK})	Boiler power 4300 W
--	-------------------------------

Voltage 220-240 V / 380-415 V (3N)	Frequency 50/60 Hz
--	------------------------------

3 GROUPS TALL

Dimensions (W×D×H) 39.6×20.9×25.2 in	Weight 209 lb
--	-------------------------

Boiler 16 l (3.5 gal _{UK})	Boiler power 6000 W
--	-------------------------------

Voltage 220-240 V / 380-415 V (3N)	Frequency 50/60 Hz
--	------------------------------

STANDARD

1 filter holder for 2 cups per group, 1 filter holder for 1 cup, cuprest-tray, 2 steam wands, 1 hot water dispenser, cup warmer, filters

OPTIONAL

Milk frother, Filter holder for pod, gas heating, pod kit, capsule kit, Milk Temperature Sensor (MTS), Easy Steam Milk (ESM), LED lights

ACCESSORIES

Automatic or manual water softener, MD dosing grinder

COLORS

Gloss black

FEATURES | ON DEMAND

Portafiltro per cialda € 89,00
Filter holder for pod

ESM € 147,00
Easy Steam Milk

Luci LED per 2 gruppi € 164,00
LED Lights for 2 groups

Luci LED per 3 gruppi € 208,00
LED Lights for 3 groups



GREEN ME TALL 2GR

€ 4.820,00



GREEN ME TALL 3GR

€ 5.948,00

Per info su Certificazioni Prodotti disponibili visitare www.promacitalia.com
For info on available Products' Certifications please visit www.promacitalia.com

GREEN CLUB ME / PU / PU-S

CARATTERISTICHE TECNICHE

1 GRUPPO ME

Dimensioni (LxPxA) 385x530x560 mm	Peso 34 kg
Caldaia 4 l	Potenza caldaia 1700 W (1600 W)
Voltaggio 220-240 V / (120 V)	Frequenza 50/60 Hz

1 GRUPPO PU

Dimensioni (LxPxA) 385x530x560 mm	Peso 34 kg
Caldaia 4 l	Potenza caldaia 1700 W (1600 W)
Voltaggio 220-240 V / (120 V)	Frequenza 50/60 Hz

1 GRUPPO PU-S

Dimensioni (LxPxA) 385x530x560 mm	Peso 34 kg
Caldaia 4 l	Potenza caldaia 1700 W (1600 W)
Voltaggio 220-240 V / (120 V)	Frequenza 50/60 Hz

Serbatoio acqua interno
2 l - con addolcitore

DOTAZIONI

1 portafiltro per due caffè, 1 portafiltro per un caffè,
1 erogatore vapore, 1 erogatore acqua calda, filtri

OPTIONAL

Portafiltro per cialda, kit caldaia, kit capsula

ACCESSORI

Addolcitore d'acqua automatico o manuale,
macinadosatore MD

COLORI

Grigio, nero lucido, rosso bordeaux

TECHNICAL FEATURES

1 GROUP ME

Dimensions (WxDxH) 15.2x20.9x22.0 in	Weight 75 lb
Boiler 4 l (0.9 gal _{UK})	Boiler power 1700 W (1600 W)
Voltage 220-240 V / (120 V)	Frequency 50/60 Hz

1 GROUP PU

Dimensions (WxDxH) 15.2x20.9x22.0 in	Weight 75 lb
Boiler 4 l (0.9 gal _{UK})	Boiler power 1700 W (1600 W)
Voltage 220-240 V / (120 V)	Frequency 50/60 Hz

1 GROUP PU-S

Dimensions (WxDxH) 15.2x20.9x22.0 in	Weight 75 lb
Boiler 4 l (0.9 gal _{UK})	Boiler power 1700 W (1600 W)
Voltage 220-240 V / (120 V)	Frequency 50/60 Hz

Internal water tank
2 l (0.4 gal_{UK}) - with built-in softener

STANDARD

1 filter holder for 2 cups, 1 filter holder for 1 cup,
1 steam wand, 1 hot water dispenser, filters

OPTIONAL

Filter holder for pod, pod kit, capsule kit

ACCESSORIES

Automatic or manual water softener,
MD dosing grinder

COLORS

Natural grey, gloss black, bordeaux red

FEATURES | ON DEMAND

Portafiltro per cialda € 89,00
Filter holder for pod



GREEN CLUB ME 1GR
€ 2.142,00



GREEN CLUB PU 1GR
€ 1.911,00



GREEN CLUB PU-S 1GR
€ 1.806,00

Per info su Certificazioni Prodotti disponibili visitare www.promacitalia.com
For info on available Products' Certifications please visit www.promacitalia.com

K65 AT / ST / OD

CARATTERISTICHE TECNICHE

K65 AT (automatica) / K65 ST (semi-automatica)

Dimensioni (LxPxAl) 220x385x575 mm	Peso 13 kg
Dose regolabile 5,5-10 g	Produzione 7-9 kg/h
Diametro macine 64 mm	Contenitore grani caffè 1,3 kg
Voltaggio 110 V - 230 V	Frequenza 50/60 Hz
Potenza 450 W	Versioni semi-automatica ST automatica AT

K65 OD (on demand)

Dimensioni (LxPxAl) 220x385x575 mm	Peso 13 kg
Giri motore 1350 rpm	Produzione 3,5 g/s
Diametro macine 64 mm	Contenitore grani caffè 1,3 kg
Voltaggio 110 V - 230 V	Frequenza 50/60 Hz
Potenza 450 W	

TECHNICAL FEATURES

K65 AT (automatic) / K65 ST (semi-automatic)

Dimensions (WxDxH) 8.7x15.1x22.6 in	Weight 28.7 lb
Variable dose 0.19-0.35 Oz (5,5-10 g)	Production 15.4-19.8 lb/h (7-9 kg/h)
Grinding burrs diameter 2.52 in (64 mm)	Coffee bean container 2.9 lb (1.3 kg)
Voltage 110 V - 230 V	Frequency 50/60 Hz
Power 450 W	Version semi-automatic ST automatic AT

K65 OD (on demand)

Dimensions (WxDxH) 8.7x15.1x22.6 in	Weight 28.7 lb
Motor speed 1350 rpm	Production 0.12 oz/s (3.5 g/s)
Grinding burrs diameter 2.52 in (64 mm)	Coffee bean container 2.9 lb (1.3 kg)
Voltage 110 V - 230 V	Frequency 50/60 Hz
Power 450 W	

OPTIONAL | K65 OD

Pressino per Caffè € 76,00
Coffee Tamper



K65 AT
€ 853,00
K65 ST
€ 742,00



K65 OD
€ 1.054,00

MD 75 / 74 / CLUB

CARATTERISTICHE TECNICHE

MD 75 AT (automatica)

Dimensioni (LxPxA) 200x390x610 mm	Peso 22 kg
Produzione 12-14 kg/h	Contenitore grani caffè 1,4 kg
Diametro macine 75 mm	Potenza 950 W
Voltaggio 110 V / 230 V / 400 V 3N	Frequenza 50/60 Hz

MD 74 AT (automatica)

Dimensioni (LxPxA) 200x310x630 mm	Peso 22 kg
Produzione 13-15 kg/h	Contenitore grani caffè 1,5 kg
Diametro macine coniche 68 mm	Potenza 250 W
Voltaggio 110 V / 230 V / 400 V 3N	Frequenza 50/60 Hz

MD CLUB (semi-automatica)

Dimensioni (LxPxA) 140x335x440 mm	Peso 9 kg
Produzione 2,5-3,5 kg/h	Contenitore grani caffè 0,5 kg
Diametro macine 50 mm	Potenza 140 W
Voltaggio 110 V / 230 V	Frequenza 50/60 Hz

TECHNICAL FEATURES

MD 75 AT (automatic)

Dimensions (WxDxH) 7.9x15.3x24.0 in	Weight 48.5 lb
Production 26.4-30.9 lb/h (12-14 kg/h)	Coffee bean container 49.4 Oz (1.4 kg)
Grinding burrs diameter 2.9 in (75 mm)	Power 950 W
Voltage 110 V / 230 V / 400 V 3N	Frequency 50/60 Hz

MD 74 AT (automatic)

Dimensions (WxDxH) 7.9x12.2x24.8 in	Weight 48.5 lb
Production 28.7-33.1 lb/h (13-15 kg/h)	Coffee bean container 52.9 Oz (1.5 kg)
Conic grinding burrs diameter 2.7 in (68 mm)	Power 250 W
Voltage 110 V / 230 V / 400 V 3N	Frequency 50/60 Hz

MD CLUB (semi-automatic)

Dimensions (WxDxH) 5.5x13.2x17.3 in	Weight 19.8 lb
Production 5.5-7.7 lb/h (2.5-3.5 kg/h)	Coffee bean container 17.6 Oz (0.5 kg)
Grinding burrs diameter 2.0 in (50 mm)	Power 140 W
Voltage 110 V / 230 V	Frequency 50/60 Hz



MD 75 AT
€ 1.050,00



MD 74 AT
€ 2.384,00



MD CLUB
€ 530,00

Per info su Certificazioni Prodotti disponibili visitare www.promacitalia.com
For info on available Products' Certifications please visit www.promacitalia.com

CARATTERISTICHE TECNICHE

DP 190

Dimensioni (L×P×A)	Quantità resina	Quantità sale
240×405×620 mm	8 l	25 kg
Attacco gas	Pressione di servizio	
3,4" gas retro	1,5-6 bar	

DP 100

Dimensioni (L×P×A)	Quantità resina	Quantità sale
200×325×485 mm	4 l	10 kg
Attacco gas	Pressione di servizio	
3,8" gas laterale	1,5-6 bar	

DP 12

Dimensioni (Ø×A)	Quantità resina	Quantità sale
180×560 mm	9 l	–
Attacco gas	Pressione di servizio	
3,8" gas	1-8 bar	

DP 8

Dimensioni (Ø×A)	Quantità resina	Quantità sale
180×440 mm	5,8 l	–
Attacco gas	Pressione di servizio	
3,8" gas	1-8 bar	

TECHNICAL FEATURES

DP 190

Dimensions (W×D×H)	Resin quantity	Salt quantity
9.4×15.9×24.4 in	8 l (1.76 gal _{UK})	55 lb
Gas connection	Service pressure	
3.4" gas back	1.5-6 bar	

DP 100

Dimensions (W×D×H)	Resin quantity	Salt quantity
7.9×12.8×19.1 in	4 l (0.88 gal _{UK})	22 lb
Gas connection	Service pressure	
3.8" gas lateral	1.5-6 bar	

DP 12

Dimensions (Ø×H)	Resin quantity	Salt quantity
7.1×22.0 in	9 l (1.98 gal _{UK})	–
Gas connection	Service pressure	
3.8" gas	1-8 bar	

DP 8

Dimensions (Ø×H)	Resin quantity	Salt quantity
7.1×17.3 in	5.8 l (1.27 gal _{UK})	–
Gas connection	Service pressure	
3.8" gas	1-8 bar	



DP 190
€ 1.187,00



DP 100
€ 998,00



DP 12
€ 179,00

DP 8
€ 163,00

CONDIZIONI GENERALI DI VENDITA GENERAL CONDITIONS OF SALES

Decorrenza. Il presente listino entra in vigore il 09/01/2017. Non costituisce offerta e ad esso possono essere apportate in qualsiasi momento, senza alcun obbligo di preavviso, tutte le modifiche di prodotto e di prezzo.

Prezzi. I prezzi, espressi in euro, sono quotati al pubblico IVA esclusa per merce imballata franco fabbrica, esclusa l'installazione.

Resa. La resa è da considerarsi presso lo stabilimento Rancilio. La merce, comunque spedita, viaggia ad esclusivo rischio dell'acquirente e pertanto non si riconoscono danneggiamenti o perdite durante il trasporto.

Garanzia. La merce è garantita dal costruttore per 12 mesi dalla data installazione contro i difetti originari di fabbricazione. La garanzia non comprende i danni derivanti da installazioni o manutenzioni scorrette. La Rancilio Group spa con socio unico non può essere considerata responsabile per eventuali danni causati da usi impropri, erronei o irragionevoli dei propri prodotti. La garanzia ha valore unicamente nei confronti dell'acquirente originario ed è relativa solo ed esclusivamente ai pezzi di ricambio, la manodopera relativa ad interventi sui prodotti non è coperta dalla presente garanzia. L'eventuale restituzione dell'apparecchiatura deve essere autorizzata per iscritto dalla Rancilio Group spa con socio unico. La validità della garanzia è subordinata al puntuale rispetto delle scadenze di pagamento del prezzo di acquisto; in mancanza di esso la garanzia viene concessa esclusivamente ad insindacabile giudizio dell'azienda.

Controversie. Per ogni controversia è competente il foro di Milano.

Entry in effect. This price list will take effect as of 09/01/2017. It does not represent a tender and all products and prices are subject to change at any time without notice.

Prices. The prices are expressed in Euros; prices to the public are quoted net of VAT for goods packaged ex-works, installation excluded.

Terms of delivery. The delivery is to be considered in Rancilio factory. The buyer bears all transport risks, however the goods are shipped, and thus the manufacturer will not be liable for damage or losses occurring during transport.

Warranty. The manufacturer provides a warranty for manufacturing faults for the merchandise for 12 months from the date of installation. The warranty does not cover damages caused by incorrect installation or maintenance. Rancilio Group spa con socio unico shall not be held liable for any damages caused by improper, erroneous or unreasonable use of its products. The warranty shall only be valid for the original purchaser and it shall only cover parts; it does not cover the labor. Any return of the equipment must be authorized in writing by Rancilio Group spa con socio unico. The validity of the warranty is subordinated to the full respect of the purchase price payment deadlines; in absence of such respect the warranty will be granted at the sole discretion of the company.

Disputes. Any disputes shall be settled by the Court of Milan, Italy.

CONTATTI CONTACTS

HEADQUARTERS, PRODUCTION PLANT AND R&D CENTERS

Rancilio Group S.p.A. con socio unico
Viale della Repubblica 40
20015 Villastanza di Parabiago (MI) - Italy
Ph. +39 0331 408200
Fax +39 0331 551437
info@ranciliogroup.com

www.promacitalia.com | www.ranciliogroup.com



www.facebook.com/promacitalia



Promac Italia Channel



www.instagram.com/promacitalia



RANCILIOGROUP

an Ali Group Company



The Spirit of Excellence